Plataforma sobre Adaptación al Cambio Climático en España
Published on Plataforma sobre Adaptación al Cambio Climático en España (https://adaptecca.es)
Home > Urban stormwater management in Augustenborg, Malmö

Urban stormwater management in Augustenborg, Malmö

[1]

Image of from Climate Ardapt about this case study

[2]

Autor: © TCPA

During the 1980s and 1990s, the neighbourhood of Augustenborg in Malmö was an area of social and economic decline and was frequently flooded by an overflowing drainage system. Between 1998 and 2002, the area was regenerated. The physical changes in infrastructure included the creation of sustainable urban drainage systems (SUDS), including 6 Km of water channels and ten retention ponds.

The rainwater from roofs, roads and car parks is channelled through trenches, ditches, ponds and wetlands, with only the surplus being directed into a conventional sewer system. Green roofs have been installed on all developments built after 1998, and retrofitted on more than 11,000 m² of rooftops on existing buildings. As a result, problems with flooding have ceased and the image of the area has been significantly improved.

Case Study Description

Challenges:

The Augustenborg neighbourhood has suffered from annual flooding in the late 1990s, caused by the old drainage system being unable to cope with the combination of rainwater run-off, household waste water and pressure from other parts of the city. Resulting flooding was leading to damaging underground garages and basements, and restricted access to local roads and footpaths. Untreated sewage also often entered watercourses as a result of increasing pressure on the sewage treatment works.

Under the changing climate, precipitation is expected to increase to up to 40% in Sweden, depending on the scenario. The annual precipitation in southernmost Sweden is expected to increase roughly 15-20% by the end of the century under the RCP 8.5 scenario (SMHI [3]). Increase in precipitation is particularly high in winter and spring. This is likely to exacerbate the problems associated with rain water runoff management in urban areas.

In addition, Augustenborg, one of the first housing estates delivered under Sweden's social housing policy in the 1950s, was characterised by high levels of unemployment, high turnover of residents and high percentage of immigrants. It was an area of social and economic decline.

Objectives:

The regeneration efforts in Augustenborg started in the 1990s, and developed into the Ekostaden (Eco-city) Augustenborg project. The key aim of the initiative was to create a more socially, economically, and environmentally sustainable neighbourhood. Whilst adaptation to climate change was initially not an explicit driver, the project aimed to address the issue of urban flooding in combination with measures aiming at reductions in CO2 emissions, and at improved waste management.

Due to recurring flooding problems it was proposed that stormwater from Augustenborg should be disconnected from the existing combined sewer, and drained by means of an open system. The main intention was that 70% of the stormwater from roofs and sealed areas should be handled in the open system, eliminating combined sewer overflow completely, by both lowering the total volume of stormwater reaching pipes and reducing the peak flow rates.

Solutions:

While no climate change analysis was carried out on the open stormwater system, it was designed to accommodate a 15 year rainfall event as the baseline, which also serves the purpose of adaptation to increased precipitation in the future. The project involved retrofitting SUDS within existing development and infrastructure, and with residents in situ.

The completed stormwater management system includes a total of 6 km of canals and water channels and ten retention ponds. Rainwater is collected in natural ditches and reservoirs and then the surplus is directed to a conventional sewer system and a nearby watercourse. The rainwater from roofs, roads and car parks is channeled through visible trenches, ditches, ponds and wetlands. These landscape features are integrated into the townscape within 30 courtyard areas, which also provide recreational green spaces for the area's residents. Whilst green spaces were increased in size and number, the specific style of the 1950's was maintained so as not to compromise the aesthetics of the area. Some of the green spaces can be temporarily flooded, which helps to manage water by slowing its entry into the conventional stormwater system.

Supplementing the sustainable drainage system, there are more than 11,000 m2 of green roofs in the area, including 2,100 m2 on the buildings of the public housing company MKB and the 9,000 m2 of the Botanical Roof Garden that has been built on an old industrial building. In the regeneration project, launched in 1998, green roofs were installed on all new developments (built post 1998) and retrofitted on some older buildings, such as garages that have been turned into offices. Some newer green roofs have been installed also after the regeneration project.

As a result of the implementation of the open stormwater management system, many floods have been avoided in the area. It suggests that the design of the open stormwater system is performing better than a conventional system and that Augustenborg is well prepared for more intense rainfall events also in the future. In the summer of 2007, a 50-year rainfall event caused severe problems in most of Malmö by flooding access roads, but Augustenborg was unaffected. Again in 2014, severe flood-damages and repair cost were avoided in Augustenborg during a heavy rainfall event with over 100 mm of rain in 6 hours. Additionally, many smaller heavy precipitation events have been handled well by the open stormwater system.

It is estimated that 90% of the stormwater from the rooftops and other impervious surfaces is led into the open stormwater system. In addition, the total annual runoff volume is reduced by about 20% compared to the conventional system. This is due to evapotranspiration from channels and retention ponds between the rain events. Also, the runoff peak flows are delayed and attenuated. The implementation of an open stormwater system at Augustenborg has improved not only stormwater management in the area, but also the performance of the combined sewer system that serves the surrounding area. The volume of stormwater draining into the combined system is now negligible, and this system now drains almost only wastewater.

The alternative option of reducing flooding via a conventional separated stormwater system for Augustenborg would have meant major earthworks. This approach could also have caused problems further along the stormwater drainage network, such as bottlenecks where the system joins with older pipes. Moreover, the receiving areas could have suffered increased flood risk, erosion or water quality degradation. Therefore, the implementation of the open stormwater system was considered to be the most sustainable option aligning with the vision of the regeneration initiative Ekostaden Augustenborg.

Importance and relevance of the adaptation:

OTHER_POL_OBJ;

Additional Details

Stakeholder engagement:

The key actors involved in the regeneration of Augustenborg were the MKB housing company and the City of Malmö, represented by the Fosie district and the Service Department. However, several individuals were particularly important to the success of the project.

The process of creation of Ekostaden Augustenborg began in 1997, and was started by discussions about

closing down a nearby industrial area. The regeneration project sparked from the ideas of three active professionals from the Service department of the City of Malmö, a school in Augustenborg and the public housing company MKB. They gathered a group of senior officers, colleagues and active residents in the area who all wanted to turn the area into a sustainable district of Malmö. A project leader was hired in 1998. As the project progressed, local businesses, schools and the industrial estate became involved. The Botanical Roof Garden was developed in a partnership with several universities and private companies.

One of the main objectives of Ekostaden Augustenborg was to enable residents to play a significant role in the planning and implementation of the initiative. The Augustenborg project incorporated extensive public consultation. This included regular meetings, community workshops, and informal gatherings at sports and cultural events. The approach became increasingly open and consultative. Approximately one fifth of the tenants in the area have participated in dialogue meetings about the project, and some have become very active in the development of the area. Augustenborg school pupils were involved in a number of local developments, for example with the planning of a rainwater collection pond which is adaptable to an ice rink. Constant communication and in-depth community involvement enabled the project to accommodate residents' concerns and preferences regarding the design of the stormwater system. Consequently, the project encountered little opposition.

Still, more than 20 years from launching the regeneration project, the residents have an active role in the development of the area. Local groups of people organize activities in the area, such as urban farming, outdoor education for children and youth, and an annual celebration of the Eco-city Augustenborg (Ekostadens dag).

Success and limiting factors:

Challenges to implementation of SUDS in Augustenborg include:

- Finding physical space to incorporate the SUDS into the already existing development: (i) the SUDS had
 to be fitted around existing electricity, water, heating and telephone infrastructure; (ii) access for
 emergency vehicles had to be maintained; (iii) many residents were concerned that large percentage of
 the accessible green space was not suitable for recreation, and that some trees were removed.
- Buildings could not be damaged by water. Thus, all SUDS were underlined with geotextile, removing the possibility for increased deep percolation and limiting the system's function to water retention rather than infiltration.
- Health and safety issues had to be solved. The SUDS were located within and in close proximity to school
 grounds posing potential risks of drowning. Concerns were also raised about the drainage channels
 posing obstacles to elderly and disabled.
- Other problems associated with the project were the unavoidable noise and dust during construction, which caused complaints from local residents. In addition, the retention ponds were prone to algae growth, and a technical solution was designed to solve this problem.

Success factors include:

- The initiative and enthusiasm of the Service Department in Malmö and housing company MKB; strong leadership by individuals from these organisations and their professional networks allowed the development of the comprehensive project. In turn, this leadership was only possible due to decentralisation of power from the city to the district level.
- The collaborative character of the project enabled joint management of the project.
- Involvement of the residents in the design phase meant that there was little opposition to the project, and resulted in sense of ownership, empowerment and raised awareness among the residents.
- Extensive funding provided by the local authorities and the housing company was another success factor.

Budget, funding and additional benefits:

The total sum invested in the physical improvements in Augustenborg and related projects was around SEK 200M (~€24M). Around half of the sum was invested by the housing company MKB. SEK 24M came from the

Swedish national government within the LIP programme, and SEK 6M for building the Botanical Roof Garden came from the EU LIFE fund. Remaining funding was mainly provided by the local authorities, principally by the City of Malmö. Management work is jointly funded through the housing company, which incorporates costs into rents, the water board through the water rates, and the city council's standard maintenance budgets.

The maintenance costs of the sustainable drainage system are roughly double the amount of regular sewage system. The open stormwater system collects a lot of rubbish and weeds, and the canals are somewhat difficult to clean up and mow around. Occasionally, there can also be repair costs as the granite blocks sometimes break. However, due to the effective drainage system, some potential costs of flood-damages have been avoided in the area (see section about Solutions). The open drainage system in Augustenborg has been evaluated to be more sustainable than a traditional sewage system in technical, environmental, economic and social aspects.

In addition to adaptation to more extreme rainfall events, a range of other benefits stemmed from the comprehensive regeneration project of the Augustenborg area:

- Reconfiguration of public spaces between housing blocks has given residents opportunities to grow their own food in small allotments, and has created places for leisure and attractive areas for children to play.
- Biodiversity in the area increased. The green roofs, predominantly the Botanical Roof Garden, have attracted birds and insects, and the open stormwater system provides better environment for the local plants and wildlife. In addition, flowering perennials, native trees and fruit trees were planted, and bat and bird boxes were installed.
- The participatory character of the project sparked interest in renewable energy and in sustainable transport among residents.
- The turnover of tenancies has decreased by 20%.
- During the project implementation in 1998-2002 unemployment decreased from 30% to 6% (to Malmö's average) and participation in elections increased from 54% to 79%.

As a direct result of the project, three new local companies have started in the area: Watreco AB (set up by local resident and amateur water enthusiast), the Green Roof Institute, and a carpool company which uses ethanol hybrid cars to further reduce CO₂ emissions and other environmental impacts. Later on, the carpool company of Augustenborg has become a part of the citywide Sunfleet car sharing system.

Implementation time:

The project was started in 1997, and implemented between 1998 and 2002. The work on the SUDS infrastructure began in December 1999, and finished in the summer of 2000. The system has been operational since May 2001. Maintenance of the drainage system continues as usual in residential areas.

Reference Information

www.greenroof.se [5]

Contact:

Helen Johansson Scandinavian Green Roof Institute E-Mail: helen@greenroof.se [4]

Websites:

https://smartcitysweden.com/best-practice/329/eco-city-augustenborg-crea... [6]

https://naturvation.eu/nbs/malmo/eco-city-augustenborg [7]

https://greenroof.se/en/eco-city/botanical-garden [8]

Sources:

Green and Blue Space Adaptation for Urban Areas and Eco Towns (GRaBS), Malmö city and Scandinavian Green Roof Institute

Start here

What is AdapteCCa?

What is climate change?

What is the adaptation to CC?

What I can do?

Participate in AdapteCCa

Subjects and territories

Divulgation

Videos

Image bank

Infographics

Divulgative resources search engine

Interactive climate change adaptation dossier

Experiences of adaptation (multimedia resources)

Virtual classroom

Tools

Viewer of Climate Change Scenarios

Case Studies

Documentary search engine

Other

Participate in AdapteCCa

Source URL: https://adaptecca.es/en/urban-stormwater-management-augustenborg-malmo **Links**

- [1] https://adaptecca.es/en/urban-stormwater-management-augustenborg-malmo
- [2] https://adaptecca.es/sites/default/files/11181520.jpg

- [3] https://www.smhi.se/en/climate/future-climate/climate-scenarios/
- [4] mailto:helen@greenroof.se
- [5] http://www.greenroof.se
- [6] https://smartcitysweden.com/best-practice/329/eco-city-augustenborg-creating-an-attractive-and-resilient-district/
- [7] https://naturvation.eu/nbs/malmo/eco-city-augustenborg
- [8] https://greenroof.se/en/eco-city/botanical-garden